ELCO Lighting

Project name:

Fixture type:

Date:

Flexa™ 4" Round Reflector for Koto™ Module

Mix and match any ring finish with any reflector or baffle finish

Features

- 2 Piece Flexa™ trims for maximum design flexibility.
- Convenient twist-lock design for ease of installation.
- Diecast construction for lasting quality.
- 5″ O.D. - 3 1/8" I.D. - 1 1/8" H
- 35° Adjustability

Specifications

Damp Location UL Listed

Technical Details

Construction: Diecast aluminum with a powder coated finish.

Installation: Twist-lock design allows for easy mounting onto the Koto™ LED Module. Clips securely mount trim into the housing and keeps ring flush with ceiling.

Lamp: Koto™ LED Module.

Dimensions:





Options

All Black

All Bronze

Black Reflector w/ White Ring

Chrome Reflector w/ White Ring

Haze Reflector w/ White Ring

Chrome Reflector w/ Chrome Ring

Chrome Reflector w/ Nickel Ring

All Copper

Product Number

Item	Finish
ELK4721HW	Haze w/White Ring

Product Number Builder

Example: **ELK4721WW**

4" Koto™ Flexa™ Trim	Style	Style Finish	Ring Finish
ELK472			
	1 Reflector	**W** White	**W** White
		B Black	**B** Black
		BZ Bronze	**BZ** Bronze
		C Chrome (Reflector only)	**C** Chrome
		H Haze (Reflector only)	**N** Nickel
		CP Copper	**CP** Copper

© ELCO Lighting 2022. All rights reserved • Rev. 17 Dec 2021 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products

For use with **4″ Koto™ Twist-&-Lock Trims**

Koto™ LED Module



Koto™ LED Module
ELK07 - ELK09

PRODUCT NUMBER BUILDER

Koto™ LED Module	Lumens	Color Temperature	Beam Angle
ELK			
	07 750 lm	**27** 2700K	**(blank)** 38° lens (Standard)
	09 950 lm	**30** 3000K	**-S** 18° lens
		35 3500K	**-N** 25° lens
		40 4000K	**-W** 60° lens
		SD Sunset Dimming (ELK09 Only)	

ACCESSORIES

Lens

EP731C	18° Lens
EP732C	25° Lens
EP733C	38° Lens
EP734C	60° Lens

**EP732C, EP733C, EP734C Included*

Reflectors

EP735C	15°
EP736C	25°
EP737C	38°
EP738C	60°

Secondary Optics

L45	Hex Louver
L46	Linear Louver
L47	Spread Louver

4″ Koto™ Dedicated LED ICA Housings



4″ ICA Maximum Adjustability Housing
New Construction

CAT NO.	SPECIFICATIONS
EL485ICA	Maximum Adjustability



4″ ICA Housing
New Construction

CAT NO.	SPECIFICATIONS
EL490ICA	
EL490ICA-EM5	Emergency Battery Back-up (90 minutes)

4″ ICA Housing
Remodel

CAT NO.	SPECIFICATIONS
EL490RICA	

2-Hour Fire Rated 4″ ICA Housing
New Construction

CAT NO.	SPECIFICATIONS
EL48FICA	7 ½″ Height - Sound Rated

© ELCO Lighting 2022. All rights reserved • Rev. 17 Dec 2021 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products

For use with **4″ Koto™ Twist-&-Lock Trims**

Koto™ Architectural LED Light Engine



Koto™ LED Light Engine
ELK19 - ELK21

PRODUCT NUMBER BUILDER

Koto™ LED Light Engine	Lumens	Color Temperature	Beam Angle
ELK			
	19 750 - 850 lm	**27D** 2700K	**(blank)** 38° lens (Standard)
	21 1100 - 1500 lm	**30D** 3000K	**-S** 18° lens
		35D 3500K	**-N** 25° lens
		40D 4000K	**-W** 60° lens
		SD Sunset Dimming (ELK19 Only)	

ACCESSORIES

Lens

EP731C	18° Lens
EP732C	25° Lens
EP733C	38° Lens
EP734C	60° Lens

**EP732C, EP733C, EP734C Included*

Reflectors

EP735C	15°
EP736C	25°
EP737C	38°
EP738C	60°

Secondary Optics

L45	Hex Louver
L46	Linear Louver
L47	Spread Louver

4″ Koto™ Architectural Recessed Housings



4″ High Lumen Maximum Adjustability ICA Housing
1500 lm (18.9W) w/ELK21 Series Module
Not for use with ELK19 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E4LK79ICAD	120/277V - 0-10V/Triac/ELV



4″ Shallow Maximum Adjustability ICA Housing
850 lm (14.7W) w/ELK19 Series Module
1100 lm (14.7W) w/ELK21 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E4LK98ICA	120V - Triac/ELV
E4LK99ICAD	120/277V - 0-10V/Triac/ELV

4″ Standard ICA Housing
750 lm (11.8W) w/ELK19 Series Module
950 lm (11.8W) w/ELK21 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E4LK87ICA	120V - Triac/ELV
E4LK87ICA-EM1	Emergency Battery Back-Up
E4LK88ICAD	120/277V - 0-10V/Triac/ELV
E4LK88ICAD-EM1	Emergency Battery Back-Up

4″ Standard ICA Housing
750 lm (11.8W) w/ELK19 Series Module
950 lm (11.8W) w/ELK21 Series Module
Remodel

CAT NO.	SPECIFICATIONS
E4LK87RICA	120V - Triac/ELV
E4LK88RICAD	120/277V - 0-10V/Triac/ELV

2-Hour Fire Rated 4″ ICA Housing
750 lm (11.8W) w/ELK19 Series Module
950 lm (11.8W) w/ELK21 Series Module
New Construction

CAT NO.	SPECIFICATIONS
ELK93FICA	120V - Triac/ELV
ELK94TFICAD	120/277V - 0-10V/Triac/ELV

2042 E. Vernon Ave., Vernon, CA 90058 • Tel (323) 231-2600 Fax (323) 231-3200 • elcolighting.com
© ELCO Lighting 2022. All rights reserved • Rev. 17 Dec 2021 • ELCO Lighting reserves the right to make specification and design changes without notice.