COLLIER 132 CHANDELIER

PRODUCT FEATURES

- From the brand formerly known as Tech Lighting
- Solid faceted crystal manufactured in Czech Republic. Custom engineered natural brass connectors
- This item is made of natural brass. It is a living finish that will patina and warm with age which adds richness. If it gets an uneven patina or spots, a brass cleaner can restore the finish
- Remote and surface mount driver options available. An optional mud-in canopy kit can be ordered separately in conjunction with the 'Remote' driver option for the most minimal ceiling appearance.
- · Contact factory for custom configurations
- For minimal ceiling appearance, order the optional mud-in canopy kit in conjunction with the 'Remote' driver. It can be viewed here

LAMPING

Includes 45.1 watt, 2486 total delivered lumens, 90 CRI 2700K or 3000K LED modules. Remote dimmable with most LED compatible ELV and TRIAC dimmers. 277V dimmable with 0-10V dimmers. Surface dimmable with ELV and TRIAC dimmers. Remote 120V or 277V. Surface 120V-277V. Can be installed on a sloped ceiling up to 45°.



Natural Brass



To view all available finish options, please visit techlighting.com

ORDERING INFORMATION

700CLR	SHAPE OR SIZE	FINISH	LAMP
	132 132	BZ DARK BRONZE	-LED927R INTEGRATED LED 90 CRI 2700K 120V (REMOTE)
		NB NATURAL BRASS	-LED927R-277 INTEGRATED LED 90 CRI 2700K 277V (REMOTE)
		N POLISHED NICKEL	-LED927S INTEGRATED LED 90 CRI 2700K 120V-277V UNIVERSAL (SURFACE)
			-LED930R INTEGRATED LED 90 CRI 3000K 120V (REMOTE)
			-LED930R-277 INTEGRATED LED 90 CRI 3000K 277V (REMOTE)
			-LED930S INTEGRATED LED 90 CRI 3000K 120V-277V UNIVERSAL (SURFACE)

700CLR			
JOB NAME	 		
NOTES			
•			



SURFACE CANOPY


COLLIER 132 CHANDELIER

SPECIFICATIONS

PRIMARY MATERIAL	Aluminum or Brass
SHADE MATERIAL	Crystal
NET WEIGHT	36 lbs
HEIGHT	140.5in
WIDTH	2in
LENGTH	2in
UP LIGHT / DOWN LIGHT / BOTH?	
WET LISTED	
DAMP LISTED	
DRY LISTED	
MIN. HANGING HEIGHT	140.5in
MAX HANGING HEIGHT	143.5in
TOTAL CORD LENGTH	
TOTAL STEM LENGTH	
STEM QTY	
SLOPED CEILING ADAPTABLE?	Yes 45° Max
GENERAL LISTING	ETL Listed
INCLUDES	

4.5" 114 mm 20 mm 3.2" 81 mm 140.5" 3569 mm 2" 51 mm

REMOTE CANOPY/MUD PLATE





LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS		2486		
WATTS		45.1		
MAX WATTAGE PER BULB		45.1W		
		120V ELV, TRIAC		
		277V 0-10V		
		Universal 120V-277V ELV, TRIAC		
CCT		2700K		
CCI		3000K		
CRI		90 CRI		
LED LIFETIME				
L70		>50000		
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		Integrated LED		
LAMP INCLUDED?		True		
WARRANTY**		5 Years		

^{*} Dimming information available at <u>www.techlighting.com/Downloads#dimming</u>

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.	Yes		
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.	N/A		

 $^{^{\}star}$ If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



^{**} Visit techlighting.com for specific warranty limitations and details.