# COLLIER 84 CHANDELIER

### PRODUCT FEATURES

- From the brand formerly known as Tech Lighting
- Solid faceted crystal manufactured in Czech Republic . Custom engineered natural brass connectors
- This item is made of natural brass. It is a living finish that will patina and warm with age which adds richness. If it gets an uneven patina or spots, a brass cleaner can restore the finish
- Remote and surface mount driver options available. An optional mud-in canopy kit can be ordered separately in conjunction with the 'Remote' driver option for the most minimal ceiling appearance.
- · Contact factory for custom configurations
- For minimal ceiling appearance, order the optional mud-in canopy kit in conjunction with the 'Remote' driver. It can be viewed <u>here</u>



Includes 28.7 watt, 1582 total delivered lumens, 90 CRI 2700K or 3000K LED modules. Remote dimmable with most LED compatible ELV and TRIAC dimmers. 277V dimmable with 0-10V dimmers. Surface dimmable with ELV and TRIAC dimmers. Remote 120V or 277V. Surface 120V-277V. Can be installed on a sloped ceiling up to 45°.



Natural Brass







Natural Brass

Polished Nickel

Dark Bronze

#### ORDERING INFORMATION

| 700CLR | SHAPE OR SIZE | FINISH            | LAMP   |
|--------|---------------|-------------------|--|
|        | 8484          | BZ DARK BRONZE    | -LED927R INTEGRATED LED 90 CRI 2700K 120V (REMOTE)                 |
|        |               | NB NATURAL BRASS  | -LED927R-277 INTEGRATED LED 90 CRI 2700K 277V (REMOTE)             |
|        |               | N POLISHED NICKEL | -LED927S INTEGRATED LED 90 CRI 2700K 120V-277V UNIVERSAL (SURFACE) |
|        |               |                   | -LED930R INTEGRATED LED 90 CRI 3000K 120V (REMOTE)                 |
|        |               |                   | -LED930R-277 INTEGRATED LED 90 CRI 3000K 277V (REMOTE)             |
|        |               |                   | -LED930S INTEGRATED LED 90 CRI 3000K 120V-277V UNIVERSAL (SURFACE) |
|        |               |                   |  |


| 700CLR   |  |
|----------|--|
| JOB NAME |  |
| NOTES    |  |
|          |  |



### **SPECIFICATIONS**

| PRIMARY MATERIAL              | Aluminum or Brass |
|-------------------------------|-------------------|
| SHADE MATERIAL                | Crystal           |
| NET WEIGHT                    | 25 lbs            |
| HEIGHT                        | 89.7in            |
| WIDTH                         | 2in               |
| LENGTH                        | 2in               |
| UP LIGHT / DOWN LIGHT / BOTH? |                   |
| WET LISTED                    |                   |
| DAMP LISTED                   |                   |
| DRY LISTED                    |                   |
| MIN. HANGING HEIGHT           | 89.7in            |
| MAX HANGING HEIGHT            | 92.7in            |
| TOTAL CORD LENGTH             |                   |
| TOTAL STEM LENGTH             |                   |
| STEM QTY                      |                   |
| SLOPED CEILING ADAPTABLE?     | Yes 45° Max       |
| GENERAL LISTING               | ETL Listed        |
| INCLUDES                      |                   |

# REMOTE CANOPY/MUD PLATE SURFACE CANOPY



#### LAMPING SPECIFICATIONS

|                       | LED LAMP | INTEGRATED LED                 | NON LED | NO LAMP |
|-----------------------|----------|--------------------------------|---------|---------|
| DELIVERED LUMENS      |          | 1582                           |         |         |
| WATTS                 |          | 28.7                           |         |         |
| MAX WATTAGE PER BULB  |          | 28.7W                          |         |         |
|                       |          | 120V ELV, TRIAC                |         |         |
|                       |          | 277V 0-10V                     |         |         |
|                       |          | Universal 120V-277V ELV, TRIAC |         |         |
| CCT                   |          | 2700K                          |         |         |
| CCI                   |          | 3000K                          |         |         |
| CRI                   |          | 90 CRI                         |         |         |
| LED LIFETIME          |          |                                |         |         |
| L70                   |          | >50000                         |         |         |
| AVERAGE BULB HOURS    |          |                                |         |         |
| FIELD SERVICEABLE LED |          |                                |         |         |
| LAMP BASE             |          | Integrated LED                 |         |         |
| LAMP SHAPE            |          | Integrated LED                 |         |         |
| LAMP INCLUDED?        |          | True                           |         |         |
| WARRANTY**            |          | 5 Years                        |         |         |

<sup>\*</sup> Dimming information available at  $\underline{www.techlighting.com/Downloads\#dimming}$ 

## T20 / T24 / JA8 INFORMATION

|   | Integrated<br>LED | Replacement LED<br>Lamp | No Lamp<br>* |
|---|-------------------|-------------------------|--------------|
| This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6/JA8.                             | Yes               |                         |              |
| This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California. | N/A               |                         |              |

 $<sup>^{\</sup>star}$  If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



<sup>\*\*</sup> Visit techlighting.com for specific warranty limitations and details.